

A METHOD OF ACQUIRING AN IMAGE OF A NON-DERMATOGLYPHIC ZONE OF THE SKIN OR OF A ZONE OF THE HAIR BY MEANS OF ACQUISITION APPARATUS INCLUDING A NON-OPTICAL SENSOR

5 The present invention relates to observing human skin or hair, in particular for the purpose of diagnosis and, where appropriate, of recommending suitable treatment.

10 The invention relates more particularly, but not exclusively, to a method enabling certain parameters of a non-dermatoglyphic zone of the skin or of a zone of the hair to be determined, and/or to establish a diagnosis.

BACKGROUND OF THE INVENTION

15 The term "non-dermatoglyphic zone of the skin" should be understood, in the meaning of the present invention, as being a zone of the skin which is substantially free from dermatoglyphs, which do not deteriorate with age. Dermatoglyphs are present in the palm regions, in particular at the ends of the fingers where they constitute fingerprints. Zones of the skin
20 that do not have dermatoglyphs deteriorate with age and present folding of mechanical origin, in the form of ridges or furrows, some of which are known as wrinkles.

25 There exists a need for means that are relatively simple and inexpensive for informing a person about the state of the skin or the hair in order to determine whether cosmetic care is necessary.

Such means must be relatively simple and inexpensive in order to be used on a large scale.

30 There also exists a need for facilitating selection of care that is appropriate given the nature and/or the state of the skin or the hair of a given person.

35 There also exists a need to have means available capable of revealing the initial effects of treatment on the skin or the hair, essentially in order to encourage the person being treated to continue with the treatment.

*This paper or fee is being deposited with
the United States Postal Service "Express
Mail Post Office to Addressee" under 37
CFR § 1.10 Mailing Label
No. EL 585709 202 US*

The image of a skin anomaly is acquired by the camera and is then sent in digital format to a remote consultation center where a dermatologist can consult it and give a diagnosis.

Furthermore, its cost is relatively high because a
camera is used, and no cosmetic application for the
system is mentioned.

The invention seeks in particular to satisfy all or some of the above-mentioned needs.

Such a non-optical sensor can obtain information concerning the microrelief of said zone.

The non-optical sensor can in particular be a non-thermal sensor.

The term "microrelief" is used to mean microscopic relief at the surface of the skin or the hair, associated in particular with the presence of folding such as wrinkles large and small, pores, dead cells, hairs,

The Applicant has found, unexpectedly, that it is possible to use an image acquired by a non-optical sensor to derive information that is useful for determining certain parameters of the skin or of the hair and/or for establishing a diagnosis of the state of the skin or of the hair and/or for revealing the result of cosmetic or other treatment.

15 In a particular implementation of the invention, the acquisition apparatus includes a non-optical sensor having an active surface that is sensitive to temperature variations.

This electrical magnitude can be measured, for example, by measuring capacitance or conductance.

The active surface is preferably defined by a plurality of individual detection cells occupying at least one row, and preferably occupying a plurality of juxtaposed rows.

35 Preferably, the acquisition device is arranged to deliver the image of the observed zone in digital form, which makes it easier, for example, to transmit the image

Also preferably, the acquisition apparatus is arranged to acquire an image of a zone that is large enough to be representative in a statistical sense, e.g. having an area that preferably lies in the range about 0.2 square centimeters (cm^2) to about 2 cm^2 , and more preferably lying in the range 0.25 cm^2 to about 1 cm^2 .

In general, static acquisition is possible whenever the active surface has a large number of individual detection cells disposed in a plurality of juxtaposed rows.

Such dynamic acquisition is preferable when the active surface is in the form of a strip of individual detection cells, with the relative displacement between the zone under study and the sensor then preferably taking place perpendicularly to the long direction of the strip.

Nevertheless, by making a plurality of simultaneous
30 acquisitions both of sensor contact pressure and of the
image of the zone under study, it is sometimes possible
to extract additional information about the structure of
the microrelief of the zone under study.

The image which is acquired can thus be a three-
35 dimensional (3D) image of the zone under study when the
sensor and/or its environment make that possible.

Image acquisition can be performed without the sensor coming into contact with the zone under study (e.g. by means of an electric field effect), or in a variant with the sensor coming into contact with the zone under study.

When image acquisition is performed with contact between the zone under study and the sensor, it is advantageous to measure the contact pressure between the sensor and the zone under study during image acquisition, since the contact area between the zone under study and the sensor, and therefore the resulting image, can vary as a function of contact pressure.

When contact pressure between the zone under study and the sensor is not measured, it is preferable for image acquisition to be performed with contact pressure that is substantially constant.

The spatial resolution of the sensor preferably lies in the range 10 micrometers (μm) to 100 μm , more preferably in the range 25 μm to 75 μm , and more preferably still is about 50 μm . In particular, the sensor can present resolution enabling it to detect portions in relief that are as small as 100 μm , or even smaller.

This resolution corresponds substantially to that of the sensors that are the most widespread which have an active surface responsive to electrical charge or to temperature variations and that are used for recognizing fingerprints, and that are consequently likely to be manufactured in large quantities at relatively low cost.

In a preferred implementation of the invention, the acquired image is processed in order to determine parameters that are characteristic of the zone under study.

The processing that is performed is preferably digital processing that does not require the intervention of a human operator, in particular of a doctor.

The result of the processing also preferably makes it possible to recommended cosmetic care product, i.e. a

Image processing can be performed remotely by transferring digital data over a network, in particular the Internet.

Images of the skin or of the hair and/or data associated with said images can be taken at successive points in time and stored on a recording medium.

A database can be consulted during image processing in order to compare the acquired image and/or associated data with stock images or data taken from a large population in order to make it easier to establish a diagnosis.

Image processing can also serve to determine a mean hair diameter when the zone under study is situated on the scalp.

The invention also provides an assembly comprising:

- image acquisition apparatus for acquiring an image of a non-dermatoglyphic zone of the skin or a zone of the hair in order to determine certain parameters of said zone and/or perform a diagnosis, said acquisition apparatus including a portable non-optical sensor arranged to be suitable for being brought into contact with a non-dermatoglyphic zone of the skin, in particular a region of the forearm or of the face, or with a zone of

- a computer tool enabling useful information to be extracted from the signals delivered by the sensor concerning the microrelief of said zone, said information relating to the state of the skin or of the hair.

a) receive images in digital form corresponding to a non-dermatoglyphic zone of the skin or to a zone of the hair;

c) establish a diagnosis on the basis of the data resulting from the image processing, optionally making use of comparison data; and

Advantageously, the computer system is also arranged in such a manner as to send an e-mail or other message to a person who has made a connection and transmitted an image of the skin, said e-mail or message informing the person about the result of the diagnosis and optionally recommending a care product.

The invention also provides a method of remote diagnosis for non-therapeutic purposes, consisting in supplying a user with detection apparatus suitable for connection to a microcomputer and/or a network, in particular the Internet, in enabling the user to acquire an image of a non-dermatoglyphic zone of the skin by means of said acquisition apparatus, in enabling the user to send said image in digital form to a remote processing center via said network, in performing diagnosis in said

processing center, in informing the user by e-mail or by any other method of transmission about the result of the diagnosis, and optionally in recommending cosmetic care and, where appropriate, in delivering to the user one or more suitable care products.

The person preferably uses the network to send an image of the skin to the processing center together with personal data for facilitating the establishment of a diagnosis, such as age, sex, nature of care products previously used, or ethnic type, where this list is not exhaustive.

The invention also provides a method of cosmetic treatment comprising the following steps:

a) acquiring an image of a non-dermatoglyphic zone of the skin or of a zone of the hair, by means of a non-optical sensor;

b) processing said image in a computer system so as to obtain a diagnosis; and

c) recommending care treatment in the light of said diagnosis.

The method can also include a step consisting in applying the recommended care product on the zone in question.

In a particular implementation of this cosmetic treatment method, the image is processed at its site of acquisition, e.g. in premises for selling or presenting goods, or at home.

In another particular implementation of this method of cosmetic treatment, the image is processed remotely, in a processing center.

Under such circumstances, the image is advantageously sent to the processing center via a network, in particular the Internet.

This cosmetic treatment method preferably also comprises the step in consisting in storing images acquired successively in time or the data that results

09909926-072004

therefrom so as to make comparisons and show up any improvements, for example.

BRIEF DESCRIPTION OF THE DRAWINGS

Other characteristics and advantages of the present invention will appear on reading the following detailed description of non-limiting implementations of the invention, and on examining the accompanying drawing, in which:

- Figure 1 is a diagram of a microcomputer connected to acquisition apparatus constituting a non-limiting embodiment of the invention;

- Figure 2 is a view analogous to Figure 1 showing the microcomputer connected to a remote processing center;

- Figure 3 is a block diagram showing one possible arrangement of the acquisition apparatus;

- Figure 4 shows the sensor mounted on a pressure-sensitive support; and

- Figure 5 shows an image of the skin obtained by means of a non-optical sensor.

MORE DETAILED DESCRIPTION

Figure 1 shows acquisition apparatus 1 of the invention connected to a microcomputer 2 via a data transmission cable 3.

The acquisition apparatus 1 is preferably implemented in miniature form, so as to make it easier to incorporate in a housing of small dimensions that can easily be handled and brought into contact with or into the immediate vicinity of the zone to be studied, e.g. a zone situated on the face or on the forearm.

As shown in Figure 3, the acquisition apparatus 1 can comprise a non-optical sensor 4 connected to an analog-to-digital converter 5 and to a control circuit 6 controlling operation of the sensor 4.

The control circuit 6 is itself connected to an interface circuit 7 enabling digital data to be exchanged with the microcomputer 2.

T00220-9266660

also advantageously being arranged to give a diagnosis and recommend a care product.

As shown in Figure 2, the microcomputer 2 can also be connected by means of a modem to a remote processing center 9 comprising a server incorporating a database or
5 suitable for communicating with a database.

The processing center 9 can be made accessible to the user by means of an Internet site, for example.

In the example of Figure 2, the user sends the image of the skin as obtained by means of the acquisition
10 apparatus 1 to the processing center 9, and the center processes the data it receives so as to deliver a diagnosis and possibly recommend a care product.

The microcomputer 2 and/or the processing center 9
15 are preferably arranged to store images that are acquired in succession, so as to enable a user to observe quickly the effects of a care product, for example.

A user can thus be encouraged to continue with treatment once signs of improvement appear, even if they
20 are invisible to the naked eye and not perceptible to an untrained person, or on the contrary the user can change treatment when it turns out to be ineffective.

The microcomputer 2 is advantageously programmed to be capable of displaying a plurality of images of the
25 skin, taken at different times, so as to enable users to make their own comparisons.

The microcomputer 2 could also be arranged to contribute to showing up changes in the microrelief of the skin between two images taken at different times.

30 In the examples described above, it is necessary to make contact between the zone under study and the sensor while acquiring the image.

Nevertheless, the invention is not limited to sensors that require contact with the zone to be
35 observed.

When contact is necessary and the image delivered by the sensor changes with changing pressure exerted by the

09909926-072004

sensor on the observed zone, it is advantageous, as shown in Figure 4, to use a suitable detector 8 on which the sensor 4 is mounted to measure the contact pressure associated with each image so as to extract 3D

5 information from the way images vary with pressure.

This makes it possible with suitable data processing to determine the profile of a wrinkle, for example.

Naturally, the invention is not limited to the examples described above.

10 In particular, the acquisition apparatus can be used to measure mean hair diameter, for example.

0909926-072004
T00220-0260660